

MASONRY ANCHOR BOLTS

Electroplated zinc finish to BS 1706 Class C (ZA2)

Masonry Drill Bits in 'Tools' section

Suitable for concrete and most types of masonry

Ideal for overhead and ceiling work

For wall fixing, provides a stud on which to hang the fixture during installation. For fixing where the bolt needs to be inserted after the shield has been positioned, e.g. installing heavy equipment or machinery

Part No.	Wt. Kg	Bolt Size	Shield Length	Fixing Thickness Min.	Hole Max.	Hole Dia.	Depth
2/MAB/0810B	0.055	M8	50	0	10	14	55
2/MAB/0825B	0.060	M8	50	0	25	14	55
2/MAB/1010B	0.097	M10	60	0	10	16	65
2/MAB/1025B	0.103	M10	60	0	25	16	65
2/MAB/1210B	0.173	M12	75	0	10	20	85
2/MAB/1225B	0.185	M12	75	0	25	20	85
2/MAB/1615B	0.408	M16	115	0	15	25	125
2/MAB/1630B	0.435	M16	115	10	30	25	125
2/MAB/0810S	0.058	M8	50	0	10	14	55
2/MAB/0825S	0.062	M8	50	0	25	14	55
2/MAB/1015S	0.099	M10	60	0	15	16	65
2/MAB/1030S	0.111	M10	60	0	30	16	65
2/MAB/1215S	0.187	M12	75	0	15	20	85
2/MAB/1230S	0.198	M12	75	0	30	20	85
2/MAB/1615S	0.430	M16	115	0	15	25	125
2/MAB/1635S	0.457	M16	115	10	35	25	125

