

FEEDER BRACKETS

Material 50 x 8mm S275JR BS EN 10025-2

Galvanized to BS EN ISO 1461 - use 12mm fixings

Pitch centres of feeder holes 65mm



Part No.	Series	Angle	Feeder Holes No. /Dia	Dev Length	Wt. Kg
30FB11204	1000	0°	4/12	463	1.4
30FB11206	1000	0°	6/12	593	1.8
30FB112456	1000	45°	6/12	593	1.8
30FB112904	1000	90°	4/12	463	1.4
30FB112906	1000	90°	6/12	593	1.8
30FB21204	2000	0°	4/12	525	1.6
30FB21206	2000	0°	6/12	655	1.9
30FB212456	2000	45°	6/12	655	1.9
30FB212904	2000	90°	4/12	525	1.9
30FB212906	2000	90°	6/12	655	2.0
30FB31204	3000	0°	4/12	563	1.7
30FB31206	3000	0°	6/12	693	2.1
30FB312456	3000	45°	6/12	693	2.1
30FB312904	3000	90°	4/12	563	1.7
30FB312906	3000	90°	6/12	693	2.2
30FB41204	4000	0°	4/12	611	2.0
30FB41206	4000	0°	6/12	741	2.3
30FB412456	4000	45°	6/12	741	2.4
30FB412904	4000	90°	4/12	611	1.9
30FB412906	4000	90°	6/12	741	2.4